

RITEGRIP – HEAVY-DUTY GRIT ANTI-SLIP TAPE

A durable anti-slip PVC tape with aluminium oxide grit surface, designed for high-traction safety applications. Resistant to water, temperature, UV, and common cleaning agents. Ideal for preventing slips in critical areas such as steps, ramps, ladders, boats, and industrial floors.

CONSTRUCTION

BACKING	100μ PVC FILM
SURFACE	60 GRIT ALUMINIUM OXIDE
ADHESIVE	50μ MODIFIED SOLVENT ADHESIVE
LINER	150μ WHITE PAPER LINER

TECHNICAL SPECIFICATIONS (TYPICAL VALUES)

TOTAL THICKNESS	0.80MM
CARRIER THICKNESS	100μ
COLOURS AVAILABLE	BLACK/WHITE/YELLOW/BLACK-YELLOW
INITIAL TACK	>18 N/25MM
HOLDING POWER	>64H
TENSILE STRENGTH	60N/25MM
ELONGATION AT BREAK	\geq25%
COEFFICIENT OF FRICTION	R13 (>0.54)

SURFACE PREPARATIONS AND FINISHING

Application temperature +10°C to +30°C (environment and substrate). Surfaces must be dry, clean and solid. Clean surfaces with an adequate cleaner. Expected level of performance will be reached after a bonding period of 24 hours. Best performance is achieved on smooth, stable surfaces.

SHELF LIFE

Store between +10°C and +30°C, 65%RH and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

WARRANTY AND GUARANTEE

Rite Adhesives warrants that its' product complies, within its shelf life, to its specifications. The values listed are typical and provided for reference. Customers must verify suitability for their intended application.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Eurotech/Rite Adhesives cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tape suitability for their own applications.